

## Connected kit, 3 actuations, Radio UP system

1054/18



### MTR1300EB-UP

- Network voltage: 230 V~(±15%)- 50 Hz
- Power on load: 5.6A - 1300W (resistive); 2.8A - 690VA (other loads)
- Consumption in standby mode:
- Room temperature: - -20°C to 60°C
- Relative humidity: 0 to 90%
- IP protection rating: IP30
- Audio level:
- Range: 250m in free field of view and without obstacles. Range is reduced by metal items, walls or partitions
- Radio protocol: Zigbee
- Maximum transmitted radio power: 10 mW
- Radio frequency band: 2400.0 - 2483.5 MHz
- Dimensions (LxHxD): 44.1 x 34.7 x 18.5 mm
- GATE-UP
- Power supply: USB DC 5V to 5.25V 2A
- Radio protocol: Zigbee
- Radio frequency band: 2400.0 - 2483.5 MHz
- Maximum transmitted radio power: 10 mW
- IP network connection: Ethernet RJ45 or Wi-Fi 2.4GHz and 5GHz
- Ambient temperature: -20°C to +40°C
- Relative humidity: 0 to 90%
- IP protection rating: IP30
- Installation: tabletop or wall-mounted

## Description

The kit allows managing up to 3 lighting points, sockets, electric locks, and automations in general, and connecting the system to the Urmet Cloud in order to manage functions via the Yokis YnO app, both locally and remotely, voice assistants, Alexa and Google Assistant, and the definition of manual or automatic scenarios.

The kit is expandable with other devices from the UP radio line to allow the Yokis system to be subsequently extended.

The kit includes:

- no. 3 item no. 4820406 - Flush-mounted time-controlled 1300W electronic toggle relay module for UP radio system, with neutral wire
- no. 1 item no. 4820411 - GATE-UP IP/radio gateway, UP radio system

## Logistic data

- Packaging quantity single: **1**
- EAN single: **8021156077823**
- Base: **107 mm**
- Height: **122 mm**
- Depth: **142 mm**