

Dome, Building&Retail ECO, AHD, 2M camera with 2.8mm fixed lens

1096/310

Product specification:

- Lens: f 2.8mm fixed
- Resolution: (AHD) 2MP@25/30fps - (CVI) 2Mp@25/30fps - (TVI) 2MP@12.5/20fps - (CVBS) 720TVL
- Sensitivity: 0.03 Lux @(F1.2,AGC ON); 0 LUX IR ON
- IR LED no./Lighting distance: 14 / max 20m IR ON
- Exposure: Automatic
- Synchronisation: Internal
- IR CUT FILTER: YES
- COAX UTC control for OSD: YES
- White balancing: ATW/MW
- Backlight compensation: GLOBAL/BLC/CENTRAL/FLT
- Gain control (AGC): ADJUSTABLE
- Digital 2D noise reduction (2DNR): YES
- Digital Wide Dynamic Range (DWDR): YES
- Rated power supply: 12 Vdc
- Maximum consumption: 500mA±5%IR ON
- Operating temperature: -20 / +55°C
- Dimensions (L x D): 80x93 mm
- Protection rating: IP66
- Use: Indoor/outdoor



67,86 Euro (VAT excluded)
Price list valid from 01/09/2024

Description

The AHD 2M camera range features simplicity of configuration and video quality. It can be used in different types of installation with coaxial cable transmission infrastructure. The camera also supports CVBS- CVI - TVI streaming technologies

Logistic data

- Packaging quantity single: **1**
- EAN single: **8021156068937**
- Base: **130 mm**
- Height: **120 mm**
- Depth: **115 mm**