



8CH, H.265 HVR Building&Retail L series, 5M

urmet

1097/578

Product specifications:

- Compression formats: Video: H.265 / H.264 - Audio: G.711a
- Video inputs: 8-CH input with BNC video / 4-CH input with IP video (up to 12-CH with IP video input) (up to 12-CH with mixed video input: Analogue + IP)
- Audio Inputs/Outputs: 8-CH RCA input / 1-CH RCA output
- Recording resolution: 5M Lite(1280x1944)/4M Lite(1280x1440)/1080P(1920x1080)/720P(1280x720)/WD1(960x576)
- Recording frame rate: Main Stream Analog 5MP-Lite:12fps (per single ch)/4MP-Lite:18fps (per single ch)/1080P:15fps (per single ch)/720P:PAL:25fps(per single ch) /NTSC:30fps (per single ch) IP: PAL:25fps (per single ch) / NTSC: 30fps (per single ch) Substream Analog Max PAL: 704x576:10fps (per single ch) NTSC:704x480:10fps (per single ch)
- IP recording bandwidth: 16Mbps ~48Mbps (default 16Mbps, for each analogue channel excluded, bandwidth increases by approx. 4Mbps)
- Maximum output bandwidth: 64Mbps
- Hard disk interface: Max. 1 SATA HDD (Max 8T)
- HD included: 1000 GB hard disk (default)
- Storage spaces: External USB device /e-SATA / Network
- Web software / Multilingual client: Internet Explorer 10/11/UVS pro
- Intelligent Video Analysis (for coaxial inputs): PID / LCD / PD / SOUND DETECTION / VIDEO TAMPERING
- Intelligent Video Analysis (*depending on IP camera model): *Perimeter Intrusion Detection (PID), *Line Crossing Detection (LCD), *Stationary Object Detection (SOD), *Pedestrian Detection (PD), *Face Detection (FD), *Cross Counting (CC), Sound Detection, Video Tampering
- Alarm I/O: 8-CH alarm Input, 1-CH alarm Output
- PDA Mobile Software: Urmet iUVS PRO (iOS, Android)
- USB ports: No.1 -2.0 + No.1 -3.0
- Ethernet: Self-adaptive interface RJ-45 10M/100MB
- Network protocols: TCP/IP, DHCP, UDP, Urmet DDNS/UrmetDDNS2 with ID, P2P, PPPOE, Cloud Storage , SMTP , HTTPS , PPPoE , FTP , RTSP , UPNP , SNMP
- BNC output: 1 Out (704x576) Only for SPOT functionality for analogue channels
- VGA output: YES
- HDMI output: YES
- Power consumption: 10.9W (6.4W without HD)
- Power supply: 12V / 2A
- Operating temperature: 0°C~+40°C / below 90%RH
- Cooling fans: NO
- Dimensions (L x H x D): 300 x 53 x 227 mm
- Weight:~3 kg

Description

La gamma HVR (Hybrid Video Recorder) AHD si caratterizza per le funzionalità più avanzate, la compatibilità con le telecamere in tecnologia Analogica, CVI, TVI, AHD e IP, e una straordinaria facilità d'uso, grazie all'intuitivo menu di gestione. Gli HVR sono completamente telegestibili sia da sistemi Windows che MAC, compatibili con il software UVS, il browser, disponibile per IE e Safari, e con l'applicazione gratuita iUVSpro che consente una comoda gestione da tutti gli smartphone e tablet sia Android che iOS. La funzione UTC consente la visualizzazione e la gestione del menù OSD delle telecamere direttamente da HVR.

Logistic data

- Packaging quantity single: **1**
- EAN single: **8021156071395**
- Base: **43 mm**
- Height: **27 mm**
- Depth: **10 mm**