

IP 3M, fixed 3.7mm, hidden camera, Building&Retail ECO

1099/204B

Product specification:

- Sensor: 2.8" CMOS
- H.264/H.265 codec
- Min. Illumination: Color 1 lux @ F1.2(AGC ON)
- Lens: 3.7mm pinhole
- Human detection: Yes
- Alarm detection area: creation of area with 6 types of polygons
- Image Control: GPIO and Video Mode, Color Mode, B&W Mode
- Privacy Zone: Yes
- DDNS and UPnP: No
- Substream Resolution: 640x360
- Substream Max frame-rate: 25fps
- Mainstream Resolution: 2304x1296, 1920x1080, 1280x720
- Mainstream Max frame-rate: 3M@15fps
- Configuration and management app: V-Stream
- Connection protocol with HVR/NVR: ONVIF, port:80
- Power supply: 12Vdc
- PoE power supply: IEEE 802.3af standard
- Dimensions (W x H x D): 60 x 100 x 25 mm
- Weight: ~320g



128,52 Euro (VAT excluded)
Price list valid from 01/09/2024

Description

The 1099/204B IP camera is characterized by simplicity of configuration, video quality and small size. It finds application in various installation contexts

Logistic data

- Packaging quantity single: **1**
- EAN single: **8021156077014**
- Base: **0 mm**
- Height: **0 mm**
- Depth: **0 mm**