

Fisheye, Building&Retail PRIME, IP, 12M camera

1099/680

Product specification:

- Codec H.265+/H.265/H.264+/H.264
- Lens: 1.6mm 360° view angle
- Sensor: 1/2.3" Progressive CMOS
- Min. Lighting: Colour 0.01 lux @ F1.6(AGC ON); B/W 0 lux @ IR ON
- Main Stream resolution: 12MP
- Triple stream
- System compatibility: ONVIF (S/T/G Profile)
- Network interface: RJ45 10M / 100M Ethernet Interface
- WDR: D-WDR
- No. of IR LEDs/Lighting distance: 3 LEDs (SMD) / up to 5m
- Protection rating: IP67
- Built-in microphone
- SD slot for SD card (not included) max. 128GB
- Power voltage: 12Vdc
- PoE power supply: Standard IEEE 802.3af
- Dimensions: Ø120 X 55mm
- Weight: ~ 400g



397,32 Euro (VAT excluded)
Price list valid from 01/09/2024

Description

Wall-, table- or ceiling-mounted, the Fisheye camera is particularly suitable for use in the residential sector as well as for video surveillance of large areas (small businesses, means of transport, etc.). An audio function is available, as well as a slot for SD cards of up to 128GB, for local video recordings. Configuration is simple and immediate allowing you to manage, even remotely, the video surveillance of your home directly from your smartphone or tablet via the new iUVS pro app

Logistic data

- Packaging quantity single: **1**
- EAN single: **8021156076307**
- Base: **0 mm**
- Height: **0 mm**
- Depth: **0 mm**