

Dome, Building&Retail Multisensor 360, IP, 32M camera

1099/801

Product specification:

- Sensor: 1/1.8 Progressive Scan CMOS (EA)
- Lens: F1.30-2.15±10%
- Sensitivity: Colour: 0.006 Lux @ (F1.2, AGC ON), B/W: 0.002 Lux @ (F1.2, AGC ON); 0 Lux with IR on/White light on
- VDECT video analysis with Face Detection FD, Human&Vehicle Detection (PD&VD), Perimeter Intrusion Detection (PID), Line Crossing Detection (LCD), Cross Counting (CC), Stationary Object Detection (SOD), Heat Map (HM), Crowd Density Detection (CD), Queue Length Detection (QD), License Plate Detection (LPD)
- Video compression: H264 / H265
- Encoding resolution: Mainstream
8MP(3840x2160),5MP(2592x1944,3072x1728),
4MP(2592x1520),3MP(2304x1296),1080P(1920x1080),
960P(1280*960),720P(1280x720)
- Substream 720P(1280x720),VGA(640x480),QVGA(320x240)
Mobilestream VGA(640x480), QVGA320x240
- 3D DNR - BLC
- DWDR
- IR LED lighting distance: 35 m(IR)/25m (white light)
- Onvif Profile - S/G/T Profile
- Audio 1In/1Out
- Alarm 2In/2Out
- SD Card slot up to 256GB
- Reset key
- Protection rating: IP67 - IK10
- Power supply: 24VAC/12VDC/PoE



2733,19 Euro (VAT excluded)
Price list valid from 01/09/2024

Description

The Multisensor camera provides for a multi-lens (with 3 or 4 lenses) capable of capturing a 360° view of the zone of interest.

Logistic data

- Packaging quantity single: **1**
- EAN single: **8021156073900**
- Base: **500 mm**
- Height: **390 mm**

Urmet S.p.A. si riserva il diritto di apportare modifiche alle proprie apparecchiature in qualsiasi momento, senza darne preavviso. L'installazione deve essere effettuata da personale qualificato e rispettando le regole relative all'installazione del materiale elettrico in vigore nel paese dove i prodotti vengono installati.