

10/100/1000M single port 30W PoE injector

3000/470

Product specifications:

- 30W output power
- 1 gigabit PoE port + 1 gigabit Ethernet port
- Input power voltage/frequency/current: 100-240Vac / 50-60Hz / 1A
- Output voltage 52 Vdc 0.6A
- Variation on load +/- 5%
- Variation on line +/- 3%
- Min. load 0.08A / Max. load 0.55A
- Transmission: 10BASE-T UTP/STP cable Cat. 3/4/5 or higher (100m)
- 100BASE-TX UTP/STP cable Cat. 5e or higher (100m)
- 1000BASE-TX UTP/STP cable Cat. 5e or higher (100m)
- Poe Standard (maximum power per port): IEEE802.3af (15.4W) / IEEE802.3at (30W)
- MTBF: 50,000 hours
- Delay time upon switch-on at 115Vac: 2s
- Rise time at 115Vac: 40ms
- Holding time at 115Vac: 5ms
- Efficiency: 80% at 100Vac / 81% at 240Vac
- Operating temperature range (-20°C to +50°C)
- Storage temperature range (-40°C to +70°C)
- Humidity: 5% - 90%
- Plastic enclosure
- Certifications: CE, RoHS
- Dimensions (L x H x D): 166 x 40 x 57 mm
- Weight: 0.2 Kg



Description

The 3000/470 is a device capable of providing a PoE power supply of up to 30W and with a self-adapting 10/100/1000 data access port. It has a protection circuit in case of overcurrents and the normal operating condition will be restored after power supply restart. Suitable in video surveillance applications to power PoE cameras.

Logistic data

- Packaging quantity single: **1**
- EAN single: **8021156074099**
- Base: **185 mm**
- Height: **130 mm**
- Depth: **45 mm**