

10/100/1000M single port 60W PoE injector

3000/471

Product specification:

- Output power 60W
- 1 gigabit PoE port + 1 gigabit Ethernet port
- Input voltage/frequency/current: 100-240Vac / 50-60Hz / 1,25A
- Output voltage 52 Vdc 1,25A
- Min. load 0,08A / Max. load 1,15A
- Poe Standard (Max power for each port): IEEE802.3af (15,4W) / IEEE802.3at (30W) / IEEE802.3bt (60W)
- LED indicator: PoE power (red) / power usage 30% 60% 90% (green)
- Network media: 10BASE-T: Cat3.4.5or more UTP(100 m)
- 100BASE-TX: Cat5e or more UTP(100 m)
- 1000BASE-TX: Cat5e or more UTP(100 m)
- MTBF: 50.000 hours
- Extended case temperature range (-20°C to +50°C)
- Storage temperature range (-40°C to +85°C)
- Relative Humidity: 5% - 95%
- Dimensions 187x40x95 (LxHxW)
- Metal shell / Protect grade IP20
- Certification CE, RoHS
- Dimension 187*40*95mm
- Weight 0,4 Kg



116,54 Euro (VAT excluded)
Price list valid from 01/09/2024

Description

The 3000/471 is a device capable of providing a PoE power supply of up to 60W and with a self-adapting 10/100/1000 data access port. It has a protection circuit in case of overcurrents and the normal operating condition will be restored after power supply restart. Suitable for connection in networks with strong electromagnetic interference and over long distances. Allows integrated transmission of real-time control signals, images, voice and data.

Logistic data

- Packaging quantity single: **1**
- EAN single: **8021156074082**
- Base: **250 mm**
- Height: **190 mm**
- Depth: **60 mm**